

MACHINE-DATA

Machinetype	: Center Lathe
Make	: ZMM
Type	: C 10 THS 4000
Year	: 2023
Control type	:
Control	:
Storage location	: ab Werk
Origin	: Bulgarien
Delivery time	: on request
Quotation	: ab Werk
Price	: on request



TECHNICAL DATA

turning diameter over bed	860 mm
turning diameter over slide rest	620 mm
turning length	4000 (1,5m,2m,3m,5m, 6m) mm
turning dia. in gap	1050 mm
bed width	560 mm
spindle nose	11
spindle bore	132 mm
transmission ratio	3
spindle turning speed - stepless	12,5-100, 50-415,150-1250 U/min
thread	76 Stufen
metrical thread cutting	0,5 - 90 mm
thread - inch	60 - 1/3 inch.
thread - module	0,125 - 22,5
Whitworth-thread	240 - 1 1/3 DP
number of feeds	150 mm/U
rapid traverse longitudinal	3800 mm/min
longitudinal feeds:	0,039 - 18 mm/U
face feeds	0,02 - 9 mm/U
face slide travel	432 mm
upper slide-adjustment	150 mm
rapid traverse of cross-rail supports	1900 mm/min
diameter of quill	105 mm
	MK 6
quill stroke	225 mm
total power requirement	18,5 kW
weight of the machine ca.	6300 kg

Center Lathe
ZMM
C 10 THS 4000
Stock no. :1100-011505



TECHNICAL DESCRIPTION

Huvema?s range of European production lathes. Fitted out with variable speed and fully protected. These machines are perfect for all industrial applications. Users are very enthousiastic about these machines! Also available in: Also available in: 1,5m, 2 m - 6 m.

*variable speed, 3 steps
rapid traverse through joystick
protective covers
halogen machine light
cooling system*

VIDEO-LINKS

WEB-LINK

https://lagermaschinen.de/maschinen-datenblatt/Center_Lathe/ZMM/C_10_THS_4000/1100-011505

Center Lathe
ZMM
C 10 THS 4000
Stock no. :1100-011505



MACHINE PICTURES

